

Wio Core

SKU 113990234



DESCRIPTION

What is the most important thing on a board? I bet the answer must be the MCU module. MCU is like the brain of a board, without which the board is useless.

At the beginning of 2016, in order to simplify the process of IoT project, we launched [Wio Link](#) on Kickstarter and it turned out a big success, right after that, we released a mini version of Wio Link --- [Wio Node](#). Since then more and more makers are interested in its MCU module---ESP8266, which is one the most famous SoC in Seeed now.

Wait! Are we talking about Wio Core? Of course we are. ESP8266 is just a chip, and a chip without auxiliary circuitry is a body without bones and skin, that is why Wio core comes to this world. Wio core is a WiFi module with ESP8266 embedded. Basically, Wio Core can be considered equivalent to ESP-WROOM-02 except that the original firmware is replaced with firmware of Wio platform. That means hardware developed from Wio Core will be totally compatible with Wio Link and Wio Node, even software of Wio platform is available for Wio core.

As just mentioned Wio Core is developed from ESP-WROOM-02, it is also FCC, CE, KCC, TELEC, LCIE and IC certified with the best FCC results for IoT modules. Considering the size is only 18mm x 20mm, it can be easily integrated into space-limited device. With a sophisticated power management system, Wio Core can operate in sleep mode, the result is extremely low power consumption. All these good features make Wio Core one of the best solutions for mobile device, wearable device and IoT application.

FEATURES

- ESP8266 embedded (FCC, CE, KCC, TELEC, LCIE and IC certified)
- Wio Link and Wio Node compatible.
- Embedded with TCP/IP network stacks, 10-bit ADC, and HSPI/UART/PWM/I2C/I2S interfaces.
- Ultra-compact size for space-sensitive situations.

SPECIFICATION

- Certificates: FCC/CE/TELEC/RoHS
- Wi-Fi protocols: 802.11 b/g/n
- Frequency range: 2.4 GHz–2.5 GHz (2400M–2483.5M)
- Operating voltage: 3.0–3.6V
- Operating current Average: 80 mA
- Operating temperature range: -40°C–125°C
- Package size: 18mm(length) × 20mm(width) × 3mm(depth) (for normal silk-reading orientation)
- Flash memory size: 4Mbyte
- Firmware: Wio Firmware with OTA capability
- User interface: Cloud Server, Android/iOS App

DOCUMENTS

- For libraries and documents, please visit our Wiki page.